

# Harlow

Harlow, an extra-European origin bovine leather, stands out with a dynamic contrast of light and dark tones, highlighting its depth. The pattern combines style with high performance, offering durability without sacrificing its timeless appeal.



THICKNESS  
0.8-1.0 mm



AVERAGE SIZE  
4.8-5.2 m<sup>2</sup>



CHROME  
TANNING



DYED  
THROUGH



PFAS  
FREE



WATER AND STAIN  
RESISTANT



SUPERIOR  
DURABILITY



CLEANING WITH WATER  
AND MILD SOAP

Test	Test method	Measurement Unit	Guaranteed
Tear strength - single edge tear	UNI EN ISO 3377-1	N	≥ 20
Colour fastness to rubbing - Dry 500 cycles	UNI EN ISO 11640:1998	Grey scale	≥ 4
Colour fastness to rubbing - Wet 250 cycles	UNI EN ISO 11640:1998	Grey scale	≥ 4
Colour fastness to rubbing - Sweat 80 cycles	UNI EN ISO 11640:1998 - 11641 (pH8)	Grey scale	≥ 4
Flex resistance - Dry 50.000 cycles	UNI EN ISO 5402	-	No damage*
Adhesion of finish - Dry	UNI EN ISO 11644	N/cm	≥ 2
Colour fastness to artificial light Exposition energy 16.000 kJ/m <sup>2</sup>	UNI EN ISO 105B02 (MET.5)	Blue scale	≥ 5
Maintainability - soiling behaviour (wine, soiling cloth, ketchup) (30')	IM	Grey scale	≥ 3
Smolder resistance, cigarette and match flame	CAL TB-117 (2013, Sec. 1) BS 5852:1979, source 0-1 BS EN 1021-1-2:2006	-	Pass

\* visible to the naked eye



85% 15%  
Biobased content range: 75%-85% Fossil



Company with Management System Certified: Quality UNI EN ISO 9001:2015, Environmental UNI EN ISO 14001:2015

